

OptiMax Thermal Cycler

Features


- Faster Speeds
- No Condensation After Overnight Cooling at 4° C
- 6-Segment block temperature Control With Users Able To Select 6-Segment Temperatures Independently
- TM Calculator
- PC Viewer
- Simple User Interface
- 3-Year Warranty



Cat. No.	Description	Unit	Price
MPC-9610	Multigene OptiMax Thermal Cycler, 96 well x 0.2mlBlock, 115V, Features: Adjustable Heated Lid, TempRange of 4 to 99°C, Ramp Rate up to 4°/3°C (heating/cooling) per sec, Pre-programmed standard protocols, Three Year Warranty.	1	\$5,575.90

Sample Capacity	1 x 96 well plate, 12 8 x 0.2mL strip tubes, 96 x 0.2mL tubes
Programmable Temperature Range	4°C to 99.9°C
Temperature Control	Calculated or block
Temperature Accuracy/Uniformity	±0.5°C/±0.5°C
Heating/cooling method	Peltier
Max. heating/cooling rate	4°C/3°C per second
Temperature range of 6-segment blocks	30°C to 99°C. Temperature of 6-segment blocks can be set independently
Maximum Temperature difference between 6-segment temperature blocks	24°C
Programmable lid temperature	6 temperature blocks in 4 x 4 well format, 60° to 65°C, 100° to 115°C
Program memory	200 complete programs
Temp. increments/decrements	Yes
Time increments/decrements	Yes
User program folders	50 sets
Password protected programs	Yes
Communication	USB and RS232 ports
Dimensions (W x D x H)	24x42 x 25cm
Weight	9kg
Electrical	240V or 120V, 50/60 Hz

Tools For Life Science Discovery



PHENIX
RESEARCH PRODUCTS

TEL: 800.767.0665

FAX: 828.670.7020

Sales@PhenixResearch.com

www.PhenixResearch.com